

Declaration of Performance
EN 13967 2015 0437-CPR-0018/15
(PG – 751 – 101 - 07)

PDM 400 Black

1. Product Type Unique identification code of the product-type:	PDM 400 black PG - 751 – 101-07
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	See lot no.
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Flexible plastic HDPE sheets for waterproofing type V according to EN 13967
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	PDM 400 BLACK Prestol Grup doel, str.Moinski pat 101, 1480 Gevgelija,Macedonia
5. Contact Address Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant see (see 4.)
6. AVCP System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	System 2+
7. Notified body (hEN) In case of the declaration of performance concerning a construction product covered by a harmonized standard:	Notified factory production control certification body No.0437 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.
8. Notified body (ETA) In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	Not relevant (see 7)

9. Declared performance

Characteristic	Unit	Performance	Test Standard
Water tightness to liquid water	Pass	Pass	EN 1928
Resistance to static loading	kg	≥20kg	EN 12730
Tensile properties:			
- Maximum tensile force	N/50 mm	≥75 md ≥80 cmd	EN 12311-2 EN 12311-2
- Elongation	%	≥30 md ≥40 cmd	
Durability of watertightness against artificial ageing	-	NPD	EN 1296 and EN 1928
Durability of watertightness exposure to chemicals	-	NPD	EN 1296 and EN 1928
Resistance to tear (nail shank)	N	≥250 md ≥250 cmd	EN 12310-1
Joint strength	N/50 mm	N.A.	EN 12317-2
Impact test	-	NPD	EN 12961
Reaction to fire		NPD	Classes in accordance with EN 13501-5
Dangerous substances	See footnote a)	-	According to national regulations

- a) In absence of European harmonized test methods, testing and declaration for the release of substances must be obtained in regards of national regulations.

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer, identified in point 4.

Signed for and on behalf of the manufacturer by:

Pero Kokochev
Managing Director